

# OUTDOOR AC TRANSFORMERS

12V  
AC

STAINLESS  
STEEL

NEMA  
3R

UL/CUL  
LISTED

MAGNETIC  
TRANSFORMER

## TR<sub>SERIES</sub>



### SPECIFICATIONS

#### TR-060 (60W)

Primary Voltage	120VAC—1A Max
Output Voltage	12VAC—5A Max
Breakers	1x5A
Frequency	60 Hz
Dimensions	8.5" x 3.5" x 3"
Weight	5 LBS

#### TR-150 (150W)

Primary Voltage	120VAC—1A Max
Output Voltage	12, 13, 14, 15 VAC
Breakers	1x15A
Frequency	60 Hz
Dimensions	15¼" x 4¾" x 5½"
Weight	15 LBS

#### TR-300 (300W)

Primary Voltage	120VAC—3A Max
Output Voltage	12, 13, 14, 15 VAC
Breakers	1x25A
Frequency	60 Hz
Dimensions	17" x 7½" x 5½"
Weight	23 LBS

# ACCESSORIES

Automatic control methods can be added to any IFX TR series transformers

### PHOTOCELL

#### PH-ST15

Photocell	Broad Surface
Turn-On	1-3fc. Adj. up to 10fc
Turn-on/off ratio	1:3
Temp. Range	-40°~158°F
Dimensions	2" x 1.5" x 3" (2" stem)



### ASTRONOMICAL TIMER



#### GM-1

Voltage	100-125VAC / 60 Hertz
Wattage	Up to 1000W tungsten
Functions	Switch on/off 7 days programmable Timer/random timer Set for holidays/security
Control	Wi-Fi/3G/4G
Dim. WxHxD	2.40"x1.39"x3.27"



### DIGITAL TIMER

#### ST-38424

Range	Once daily/repeats
On/Off	Can select hour and minute for on/off
Security Mode	Yes
Override	Switch to always on mode

